

## EDGE

Manual assembly benches



The bench is suitable for accessories and gaskets assembly. It can rotate on a central fulcrum and can be adjustable in length, thus allowing the frame rotation.

**Emmegi S.p.A.**  
Via Archimede, 10  
41019 - Limidi di Soliera (MO)  
ITALY

Tel +39 059 895411  
Fax +39 059 566286  
P.Iva/C.Fisc 01978870366  
[info@emmegi.com](mailto:info@emmegi.com)  
[www.emmegini.com](http://www.emmegini.com)

The right to make technical alterations is reserved.



### Height-extensible support surface

The ability to extend and lengthen in height allows perfect adaptation to a variety of frame types.



### Swivel work bench

The work surface swivels on a central fulcrum and can be extended in length, allowing the frame to be rotated.



### Surface in nonslip PVC

The work surfaces are covered with non-slip PVC rubber that provides secure support when positioning the frame.



### Adjustable feet

Height adjustable feet to ensure the work bench can be positioned at the required height and perfectly flush with the other products in the Dynamic Line. The feet also have holes so they can be anchored to the floor.

## EDGE / MANUAL ASSEMBLY BENCHES

## CHARACTERISTICS

|   |             |
|---|-------------|
| Work surfaces covered with rubber       | ●           |
| Height and length adjustable work bench | ●           |
| Swivel friction work bench              | ●           |
| Feet with holes for ground fixing       | ●           |
| Arm length (mm)                         | 710         |
| Arm length (mm)                         | 1.260       |
| Height (mm)                             | 760 ÷ 1.200 |
| Load capacity (kg)                      | 60          |
| Weight (kg)                             | 45          |

Included ● Available ○

emmegi S.p.A.  
Via Archimede, 10  
41019 - Limidi di Soliera (MO)  
ITALY

Tel +39 059 895411  
Fax +39 059 566286  
P.Iva/C.Fisc 01978870366  
info@emmegi.com  
www.emmegi.com

The right to make technical alterations is reserved.