



Itaca Solution

Corner crimping machines for aluminium doors/windows



The machine has two special operating heads equipped with masses in which the 2 knives are adjustable on all crimping positions. The knives move and are adjustable on the Y axis (along the profile), on the Z axis (top-bottom) and on the X axis (along the crimping direction). These conditions prevent the replacement of tools on the machine regardless of the different types of profiles. In this way, the times and costs of placing are reduced.

ITACA SOLUTION / CORNER CRIMPING MACHINES FOR ALUMINIUM DOORS/WINDOWS

CHARACTERISTICS

Nominal pressure (bar)	7
------------------------	---

DIMENSION AND WEIGHT

Overall dimensions LxHxP (mm)	1.450 x 1.150 x 1.050
Weight (kg)	480

ACCESSORIES

Aluminium bracing clamp of 30 mm	1
Standard bracing clamp 20 mm	<input type="radio"/>
Special bracing clamp	<input type="radio"/>
Pair of standard knives, 3 mm	<input checked="" type="radio"/>
Pair of standard knives, 5 mm	<input type="radio"/>
Pair of standard knives, 8 mm	<input checked="" type="radio"/>
Pack knives set	<input type="radio"/>
Special knives set	<input type="radio"/>
Knives for Monticelli brackets	<input type="radio"/>
Support profiles	2
Support benches	<input type="radio"/>

Included ● Available ○

Emmegi S.p.A.
Via Archimede, 10
41019 - Limidi di Soliera (MO)
ITALY

Tel +39 059 895411
Fax +39 059 566286
P.Iva/C.Fisc 01978870366
info@emmegi.com
www.emmegi.com

The right to make technical alterations is reserved.