


08/12/2025





MOD-END RIFILA is a semiautomatic-cycle trimming machine for PVC frames with two controlled axes. It is equipped with a CN cutting unit with adjustable advancement speed.

TECHNICAL SHEET


08/12/2025






CN cutting unit

The cutting unit, including an integrated trim management device, is the heart of the system. It is equipped with a suction hood and in conjunction with its own exhauster ensures optimal removal of machining scraps.




Wide supporting surface

The work bench is very wide and customisable to allow the translation of even large formats. Upon request it is equipped with pneumatic bench exchange to enable on the same bench also the assembly of windows.



CN depth stop

The reference device located near the blade ensures accurate and quiet positioning of the square to be trimmed. Its adjustment range is from 0 to 70 mm. With large formats, the device automatically expands the stop dimension to ensure perfect parallelism.



Hot and cold side profile trimming

Machining on the cold side of the frame, a typical position coming out of an automatic corner cleaning machine, is best suited for in-line operation. With a properly equipped work bench, a series of perimeter assembly/final inspections/checks can be performed on the frame itself. Machining on the hot side allows for the best assessment of the quality level of the cleaning stage.



Control

The ergonomic state-of-the-art control panel features a 10.4" touchscreen display and fully customised software and is packed with functions developed in the Microsoft Windows® environment specifically for this machine. The machining cycle can be optimised by creating cutting lists, thereby reducing scrap and cycle times for workpieces loading-unloading.



Radio barcode reader (Optional)

The radio barcode reader automatically recognises the piece by means of the barcode label. Any workpiece can be loaded into the machine and the machining centre automatically prepares to perform all machining operations by reading the barcode on the label applied, greatly reducing cycle times and with no possibility of error.



Tel +39 059 895411 Fax +39 059 566286 P.Iva/C.Fisc 01978870366 info@emmegi.com www.emmegi.com

The right to make technical alterations is reserved.





MOD-END RIFILA / BENCHES FOR CNC MACHINING

2
3.100
70
20
25
2,6

CUTTING UNIT	
Rated power (kW)	2,2
Blade speed (rpm)	2.880
Blade diameter (mm)	400

FUNCTIONS Manual frame positioning

WORKPIECE LOCKING	
Pneumatic frame locking system with longitudinal hold-down device	•
Pneumatic profile alignment and straightening device	•
Workpiece reference stop near the machining unit	•
Retractable workpiece reference side stop in proximity of the machining unit for line operation	0
Profile locking dimension (mm)	40 ÷ 90
Maximum machinable square dimension - outer measurement (mm)	3.000 x 2.500
Minimum machinable square dimension - outer measurement (mm)	400 x 400
Max. machinable profile height (mm)	90
Min. machinable profile height (mm)	40
Max. machinable profile width (mm)	130
Max. machinable flap width (mm)	65

WORK BENCHES	
Contact surfaces covered with brushes	•
Work surface height (mm)	950

Included • Available O



Emmegi S.p.A. Via Archimede, 10 41019 - Limidi di Soliera (MO) ITALY

Tel +39 059 895411 Fax +39 059 566286 P.lva/C.Fisc 01978870366 info@emmegi.com www.emmegi.com The right to make technical alterations is reserved.