



Phantomatic M4 F

CNC machining centres




CNC machining centre, with 4 controlled axes; the spindle has an automatic tool slewing system that allows processing on 3 sides of the workpiece. Designed for machining bars or parts made of aluminium, PVC, light alloys in general or steel up to 2 mm. A removable front loading bench, mounted on wheels to facilitate movement, allows you to load already assembled frames into the machine and carry out processing on 4 sides. It is provided with a manual tool magazine with 9 places and a 4 places automatic tool magazine on the left side of the cabin. Optionally a second automatic tool magazine with 4 places can be added at the right side of the cabin. The workpiece or frame is positioned by a pneumatic stop positioned at the left side of the machine, and is blocked by 4 strong clamps that are positioned by the slider on the X axis. Adding a second optional stop on the right side, the machine may perform extended machining of bars up to twice the work capacity. All CNC axes are absolute and do not require resetting upon restarting the machine. Moreover it is equipped with a movable work plane for easier workpiece loading/unloading; this also allows considerable increase in the machinable section.




Operator interface

The new control version with suspended interface allows the operator to look at the monitor from any position, as it can be rotated around the vertical axis. The operator interface has a 15" touch screen display with all USB connections necessary to interface with a remote PC and NC. It has a push-button panel, mouse and keyboard. It is also set up for the connection of a barcode reader and remote push-button panel. It is equipped with a front USB socket for data transfer.



Electrospindle - M -

The 4 kW electrospindle in S1 can reach 20,000 rpm. The electrospindle movement along A axis performs -90° to +90° rotation, allowing to work on 3 sides of the profile with no need to reposition it. It can be used on profiles made of aluminium, PVC and light wood and can process extruded steel that is 2 mm thick.




Vices

The machine software can calculate the correct positioning measure for each vice unit, according to the length of the workpiece and to the type of machining to be performed. The automatic positioner allows picking all vice units and moving them by means of the gantry. This operation is performed at the highest speed and with great precision and spares longer time and collision risks, so that the machine can also be easily used by less experienced operators. The mobile work table facilitates the piece loading/unloading operation and significantly increases the machinable section.




Manual tool changer

The standard, retractable toolholder magazine can house 9 toolholder cones that can be manually taken and installed on the spindle. the position numbering allows identifying the requested tool from the hmi for each machining. the magazine is located on board the machine, in a position suitable for easy access by the operator.



Automatic left tool changer

The machine is equipped with an additional tool changer, located on the left side of the cab. It can house 4 toolholders with respective tools and adjusted as desired by the operator. the tool change is managed by the cnc according to the programmed machining.



Loading bench


The peculiar characteristic of this model is the possibility to attach a loading bench to the front part of the machine. This device allows you to load already assembled squares and machine all 4 sides, ensuring perfect alignment and support. A pneumatic system allows lifting the frame upon insertion into the machine, to easily position the profile to be machined on the vice table.





PHANTOMATIC M4 F / CNC MACHINING CENTRES

LAYOUT



The overall dimensions may vary depending on the product configuration.

AXIS STROKES

X AXIS (longitudinal) (mm)	3.000
Y AXIS (transversal) (mm)	274
Z AXIS (vertical) (mm)	390
A AXIS (electrospindle rotation)	-90° ÷ +90°

POSITIONING SPEED

X AXIS (longitudinal) (m/min)	56
Y AXIS (transversal) (m/min)	22
Z AXIS (vertical) (m/min)	22
A AXIS (electrospindle rotation) (°/min)	6.600

ELECTROSPINDLE

Maximum power in S1 (kW)	4,0
Maximum speed (rpm)	20.000
Toolholder cone	HSK-50F
Automatic tool holder coupling	●
Liquid cooling	●
Automatic tool rotation	-90° ÷ +90°




TOOL MAGAZINE

Maximum number of tools in manual magazine	9
Automatic tool magazine with 4 places (left)	●
Secondary automatic tool magazine with 4 places (right)	○
Maximum dimension of the tools that can be loaded into the magazine (mm)	Ø=80 ; L=150

WORK AREA

1F = 1 face machining

3F = 3 faces machining



	A	B	X1	Y1	Z1	X2	Y2	Z2
PHANTOMATIC M4 F	45	102	2.815	230	210	2.815	170	210
Machining within the work capacity with left automatic tool magazine	45	102	2.815	230	210	2.815	170	210
Machining within the work capacity with left and right automatic tool magazine	45	102	2.630	230	210	2.630	170	210
Extended machining with left automatic tool magazine	45	102	5.630	230	165(*)	5.630	170	165(*)
Extended machining with left and right automatic tool magazine	45	102	5.260	230	165(*)	5.260	170	165(*)

Dimensions in mm

(*) with max.admissible length tools (B = 150 mm) charged into the automatic magazine the Z value decreases to 130 mm



TAPPING CAPACITY (with Tap On Aluminium And Through Hole)

With compensator	M5
With helical interpolation	●


PROFILE POSITIONING

Workpiece reference LEFT stop with pneumatic movement	●
Workpiece reference RIGHT stop with pneumatic movement for extended machining	○

LOADING BENCH

Total dimension C: machine + loading bench (mm)	3.870
Pneumatic lifting	●
Removable bench	●
Swivel wheels	●
Maximum external dimension A of the loadable frame (mm)	2.700
Maximum profile thickness (mm)	100
Minimum internal dimension B of the loadable frame (mm)	400

LAYOUT



WORKPIECE LOCKING

Number of pneumatic vices	4
Automatic vice positioning through X axis	●

SAFETY DEVICES AND PROTECTIONS

Machine integral protection booth	●
Side tunnels	○

Included ● Available ○

Emmegi S.p.A.
Via Archimede, 10
41019 - Limidi di Soliera (MO)
ITALY

Tel +39 059 895411
Fax +39 059 566286
P.Iva/C.Fisc 01978870366
info@emmegi.com
www.emmegi.com

The right to make technical alterations is reserved.