

SPIN 4

Professional trolleys



Gasket trolley. Reel with brake and gasket-guide ensure troublefree gasket unwinding. It is equipped with a quick gasket roll change system.

Emmegi S.p.A.
Via Archimede, 10
41019 - Limidi di Soliera (MO)
ITALY

Tel +39 059 895411
Fax +39 059 566286
P.Iva/C.Fisc 01978870366
info@emmegi.com
www.emmegi.com

The right to make technical alterations is reserved.

**Reel holder**

A system of adjustable and extendable reel holders allows adaptation to the various sizes and types of reels that will be housed.

**Reel locking clutch**

The reel with clutch counteracts the unwinding phase without the possibility of running into mishaps.

**Pivoting wheels**

Equipped with 2 fixed wheels and 2 pivoting wheels with brake, which ensure a high degree of mobility and object handling ease. Locking the braking units allows their position to be fixed near different work areas.

SPIN 4 / PROFESSIONAL TROLLEYS

CHARACTERISTICS

Minimum coil reel diameter (mm)	110
Maximum reel diameter (mm)	720
Maximum reels width (mm)	250
Reel rotation clutch	●
Number of removable reels (according to model)	4
Fixture locking device complete with clutch	●
4 swivel casters, 2 of which have locking stops (mm)	Ø=125
Length (mm)	825
Width (mm)	970
Height (mm)	1.520
Load capacity (kg)	60
Weight (kg)	44

Included ● Available ○

emmegi S.p.A.
Via Archimede, 10
41019 - Limidi di Soliera (MO)
ITALY

Tel +39 059 895411
Fax +39 059 566286
P.Iva/C.Fisc 01978870366
info@emmegi.com
www.emmegi.com

The right to make technical alterations is reserved.