



TRANSIT KT

Professional trolleys



Trolley for transportation and storage of casement and finished door/ window frames. The resting base has rollers for easier handling of heavy or large size pieces.



Side contact surfaces

All contact surfaces are coated with soft nonslip PVC, which ensures the integrity of the surfaces in the housing stages.



Pivoting wheels

Equipped with 2 fixed wheels and 2 pivoting wheels with brake, which ensure a high degree of mobility and object handling ease. Locking the braking units allows their position to be fixed near different work areas.



Door sliding roller conveyor

A fixed roller conveyor allows horizontal translation of the frame by stem-mounted rollers that ensure smoothness and ease of movement.





TRANSIT KT / PROFESSIONAL TROLLEYS

CHARACTERISTICS

| | |
|---|---------|
| Compartment depth (mm) | 1.160 |
| Preparation for K-Rail track | ● |
| Number and width of compartments according to model | ● |
| Base with roller conveyor | ● |
| Soft PVC contact surface | ● |
| Handle for moving | ● |
| Wheels (mm) including two swivel wheels with brakes | Ø = 150 |

WEIGHT (DEPENDING ON MODEL)

| | |
|---------------------------|-----|
| TRANSIT KT 6-100 mm (kg) | 105 |
| TRANSIT KT 10-100 mm (kg) | 160 |
| TRANSIT KT 15-100 mm (kg) | 225 |
| TRANSIT KT 5-130 mm (kg) | 95 |
| TRANSIT KT 10-130 mm (kg) | 160 |
| TRANSIT KT 15-130 mm (kg) | 230 |
| TRANSIT KT 5-160 mm (kg) | 100 |
| TRANSIT KT 10-160 mm (kg) | 190 |

MAXIMUM LOAD CAPACITY (ACCORDING TO MODEL)

| | |
|---------------------------|-----|
| TRANSIT KT 6-100 mm (kg) | 600 |
| TRANSIT KT 10-100 mm (kg) | 740 |
| TRANSIT KT 15-100 mm (kg) | 675 |
| TRANSIT KT 5-130 mm (kg) | 500 |
| TRANSIT KT 10-130 mm (kg) | 740 |
| TRANSIT KT 15-130 mm (kg) | 670 |
| TRANSIT KT 5-160 mm (kg) | 500 |
| TRANSIT KT 10-160 mm (kg) | 710 |

Included ● Available ○