




Classic E

Double-head cutting-off machines



Electronic twin-head cutting-off machine with automatic traverse of the moving cutting head powered by brushless motor with numerical control system. Pneumatic control of the angular setting in three fixed positions 90°, 45° and 22°30' (external) or with mechanic system for manual adjustment of intermediate angles. Hydro-pneumatic blade feed.

**Mobile heads tilting**

Rotation of the heads around the horizontal axis is by means of pneumatic cylinders, and the angles that can be obtained range from 90° up to 22°30' externally; intermediate angles are obtained by means of special manually adjustable stops. Mobile units are equipped with integral pneumatic drop-down protections of the machining area.

**Control**


The control panel, installed on a support sliding on bearings along the front side of the machine, allows correct mobile heads positioning in accordance with the required cutting schedule. The interface uses a 7" touch-screen and fully personalised software and is packed with bespoke functions that are unique to this machine. The machining cycle can be optimised by creating cutting lists, thereby reducing scrap and cycle times for parts loading-unloading.

**Digital viewer for intermediate angles (Optional)**


In the presence of pneumatic tilting of the moving heads, the intermediate angle viewer allows the tilting of the cutting unit to be identified with absolute precision, ensuring the accuracy of the cut profiles. Especially useful in making out-of-square cuts, it allows the operator to quickly and accurately identify the required angle.

**Pneumatic intermediate support (Optional)**


The pneumatic intermediate support is extremely useful when cutting light profiles of considerable lengths. In this case, the pneumatic support will, automatically, provide the ideal condition to support the profile. This accessory is available for all lengths, but is specifically recommended on machines having 5- and 6-meter useful cuts.

**Electronic profile thickness gauge (Optional)**

This refined profile thickness control system enables automatic correction of the cutting dimension according to the actual size of the profile, with relative tolerance resulting from surface treatments such as painting, anodising, etc.

**Additional vice for profile support on roller conveyor (Optional)**

After each cut, the remaining profile short cut tends to fall on the roller conveyor, with the risk of hitting against the blade when the cut-off phase is still in progress. This movement may damage both the workpiece itself and the one just cut. The additional vice installed on the roller conveyor prevents this problem by keeping the profile locked for the entire duration of the cut-off cycle.


CLASSIC E / DOUBLE-HEAD CUTTING-OFF MACHINES
LAYOUT


	A
Classic E - 4 m (mm)	8.400
Classic E - 5 m (mm)	9.400
Classic E - 6 m (mm)	10.400


The overall dimensions may vary depending on the product configuration.

MACHINE CHARACTERISTICS


Electronic control of the X axis	●
X axis positioning speed (m/min)	25
Pneumatic head tilting	●
Mobile head position reading with absolute magnetic strip direct measuring system	●
External tilting	45° / 22°30'
Mechanical adjustment of intermediate angles	●
Hydropneumatic blade feed	●
Effective cut, according to model (mm)	4.000 / 5.000 / 6.000
Standard minimum cut with 2 heads at 90° (mm)	310
Minimum cut with PLUS software with 2 heads at 90° (mm)	200
Minimum push feed cut with PLUS software (mm)	0
Minimum bar scrap with push feeding (mm)	200
Cemented carbide blade	2
Blade diameter (mm)	500
Blade motor power (kW)	2,2
Loading surface height (mm)	1.140



CUTTING DIAGRAM



CUTTING UNIT TILTING



Mechanical adjustment of intermediate angles

SAFETY DEVICES AND PROTECTIONS

Pneumatically-operated front local protection

PROFILE POSITIONING AND CLAMPING

Pair of horizontal and vertical pneumatic vices with "low pressure" device	<input checked="" type="checkbox"/>
Pair of standard counterblocks	<input checked="" type="checkbox"/>
Metric ruler	<input checked="" type="checkbox"/>
Intermediate pneumatic profile support	<input type="checkbox"/>
Roller conveyor on mobile head (mm)	2.000
Additional vice for profile support on roller conveyor	<input type="checkbox"/>

**LUBRICATION AND SUCTION**

Water spray-mist lubrication system with oil emulsion or minimal diffusion oil spray-mist (depending on version)	●
Pre-setting for automatic exhaust start	●
Swarf and short cuts extractable drawers without scraper system for swarf removal (4m / 5m / 6m)	4 / 5 / 6
Dredging system for swarf discharge	○
Swarf and short cuts extractable drawers with scraper system for swarf removal	2

FUNCTIONS

Perform single cuts	●
Execution of intermediate angles cuts	●
Execution of cyclical cuts from cutting lists	●
Cutting lists import	●
Special cuts PLUS (extended cuts, short cuts, cleat cuts, bevel cuts)	○

Included ● Available ○