

05/09/2025





Trolley dedicated to vertical transportation and storage of cut profiles.

TECHNICAL SHEET

05/09/2025



emmegi :

Contact surfaces

All side and lower contact surfaces are coated with soft nonslip PVC, which ensures the integrity of the surfaces in the housing stages.



Side bins

A series of convenient bins allow for the storage of small parts in a simple and orderly manner for easy identification of items.



Pivoting wheels

Equipped with 2 fixed wheels and 2 pivoting wheels with brake, which ensure a high degree of mobility and object handling ease. Locking the braking units allows their position to be fixed near different work areas.



Emmegi S.p.A. Via Archimede, 10 41019 - Limidi di Soliera (MO)

Tel +39 059 895411 Fax +39 059 566286 P.lva/C.Fisc 01978870366 info@emmegi.com www.emmegi.com

The right to make technical alterations is reserved.









TAGLIO / PROFESSIONAL TROLLEYS

CHARACTERISTICS	
Soft PVC contact surface	•
Drawers for short pieces	4
Number of compartments	10
Compartment capacity (mm)	90 x 525
Handle for moving	•
4 low-wear swivel casters, 2 of which with locking (mm)	Ø = 125
Length (mm)	1.560
Width (mm)	960
Height (mm)	1.730
Load capacity (kg)	500
Weight (kg)	85

Included • Available O