



## V-LINK

Manual assembly benches



Vertical roller conveyor for easy transport of frames and fenestration products including very heavy ones between the various assembly stations.



### **Roller conveyor**

A roller conveyor at the base, with adjustable height from 320 to 360 mm from the ground, supports the weight of the door and ensures smoothness and ease of handling.



### **Bench with anti-scratch rollers**

Five rows of stem-mounted needle rollers form the support of the door against the inclined backrest and allow even very heavy doors to be moved safely.



### **Adjustable feet**

The height-adjustable feet ensure that the desired height of the work surface is correctly achieved and allow for a variable angle from 85° to 90°. The feet also have holes so they can be anchored to the floor.



**V-LINK / MANUAL ASSEMBLY BENCHES****CHARACTERISTICS**

|                                  |               |
|----------------------------------|---------------|
| Roller bench height (mm)         | 320 ÷ 360     |
| Adjustable roller bench tilt     | 85° ÷ 90°     |
| Weight (kg)                      | 100           |
| Load capacity (kg)               | 200           |
| Length (mm)                      | 3.000         |
| Height (mm)                      | 2.165 ÷ 3.015 |
| Width (mm)                       | 870           |
| Soft nonslip PVC contact surface | ●             |

Included ● Available ○